



DOSATRON®

Because life is powered by water®



WATER TREATMENT

D30 WATER LINE The High-flow Solution

- + Operates with water pressure - Non electric.
- + Developed for alkaline or acidic additives.
- + Easy to operate. Maintenance without tools.
- + Low pressure loss.
- + Patented technology.

**HIGH
FLOW**



D30 WL

Up to **60 l/h**
of chemical injection



ACS
Informations





Standard equipment : bleeder, suction tube, strainer, connecting flange

Versions : VF or AF seals.

Options : Manual by-pass, external injection.

Features

SPECIFICATIONS	D30WL30000 D30WL30000IE	D30WL5000
Water flow range: (min.-max.):	8 m ³ /h - 30 m ³ /h	8 m ³ /h - 30 m ³ /h
Operating water temperature:	40° C	40° C
Operating pressure: For external injection model	0.5 - 8 Bar 0.5 - 6 Bar	0.5 - 8 Bar
Injection rate %	0.003 - 0.03	0.02 - 0.2
Ratio	1:30000 - 1:3000	1:5000 - 1:500
Chemical injection flow: Min. L/h - Max. L/h US Fl. Oz/min - Min. USGPM - Max	0.24 l/h - 9 l/h 0.135 0.04	1.6 l/h - 60 l/h 0.9 0.26
Connection : CEE USA	Flange DN80 (BSP), or Threads 3» BSP 3» Threads (NPT)	

Hydraulic capacity (Motor Cylinder (2 Clicks))

1.40 Gal US (5,3l)



www.dosatron.com

This document does not form a contractual engagement on the part of Dosatron International and is for information only. DOSATRON INTERNATIONAL reserves the right to alter product specification or appearance without prior notice.

© DOSATRON INTERNATIONAL S.A.S 2018

This DOSATRON was designed to comply with the highest international approved sustainability standards.